



In House Testing Service Form

Testing Item	American Standard	Australian Standard	Chinese standard
Wide-width Tensile	ASTMD4595	AS3706.2	GB/T 15788
Grab Tensile	ASTMD4632	AS3706.2	GB/T 3923.2
Trapezoidal Tear Strength	ASTMD4533	AS3706.3	GB/T 13763
CBR Burst Strength	ASTMD6241	AS3706.4	GB/T 14800
Puncture resistance	ASTMD4833	-	GB/T 19978
Drop cone	-	AS3706.5	GB/T 17630
Flow Rate	ASTMD4491	AS3706.9	GB/T 15789
Permeability	ASTMD4491	AS3706.9	GB/T 15789
Permittivity	ASTMD4491	AS3706.9	GB/T 15789
A.O.S	ASTMD4751	AS3706.7	GB/T 14799
Thickness(Single layers)	ASTMD5199	AS2001.2.15	GB/T 13761.1
Mass per Unit	ASTMD5261	AS2001.2.13	GB/T 4669

Test capability:

Our company has advanced, complete, high precision testing equipments and excellent testing team. We can according to American standards, Australian standards, the Chinese standard for high-quality testing of geosynthetics and provide International authoritative testing report. We will provide reliable, efficient and quality service to customers.



Dalian Geo-Link Geosynthetics Co.,Ltd.

Add: No.8888-1 Southeast Industrial Zone, Youjia, Ganjingzi District, Dalian, China P.C.: 116039

Tel: +86-(0)411 6600 7883

Fax: +86-(0)411 6600 7882

WebSite: www.geo-textile.com

E-Mail: info@geo-textile.com

